

**VX65****TX45****TX65c****TX65****TX80**

Unit Weight	135kg	170kg	135kg	210kg	211kg
Tyre Breakout Force	Variable Hydraulic 125lb-625lb	Spring 550lb	Variable Hydraulic 125lb-625lb	Spring 650lb	Variable Hydraulic 800lb (Opt. 1400lb)
Heat Treated Spring Steel Tyre Dimensions	1x2" - 25x50mm	5/8x2" - 16x50mm (Opt. 1x2"-25x50mm)	1x2" - 25x50mm	1x2" - 25x50mm (Opt. 1x3"-25x75mm)	1x2" - 25x50mm (Opt. 1x3"-25x75mm)
Drum Coulter Size	*	18" Disc 13" Drum	18" Disc 13" Drum	20" Disc 15" Drum	20" Disc 15" Drum
Max Down Force	Up to 305kg	Up to 370kg	Up to 305kg	Up to 400kg	Up to 400kg
Diamond Clamp Width	158mm	160mm	158mm	200mm	200mm
Under Bar Operating Height	680mm	680mm	680mm	680mm	680mm
Opt. Double Shoot Tyne	✓	✓	✓	✓	✓
Opt. Rear Chain Harrow	✓	✓	✓	✓	✓
Opt. Press Wheel Scraper	✓	✓	✓	✓	✓
Opt. Low Draft Shank	✓	*	✓	✓	✓
Double Disc Shank Compatible	✓	✓	✓	✓	✓